

# Container 40' ISO loaded with 39 Japan pallets via DPA Duisburg

## lower level 20 pallets

### loading with

total **39 Japan pallets** 1150 x 900 mm, max. 640 kg each  
( for Article RB 35377 + RB 39084)

For protection purposes each pallet is equipped by dispatch plant with  
1 integrated carton interlayer (Art. 32502)

### tie-down

2 particle boards  
(2200 x 1033 x 10 mm)  
have to be positioned at  
the front wall of container

2 large and 2 small airbags



The airbag (900 x 1850 mm)  
for the middle blocking

The airbag (900 x 1850mm)  
has to be applied about 30 cm  
above loading platform



To protect goods against damage at the container doors  
2 particle boards (2200 x 1033 x10 mm) have to be placed  
adjacent to loaded goods and afterwards.



### picture sealed (bolt seal)



### Accessories for tie-down additionally provided by crossdocking partner

- 11x Art. 32396 Airbag large (1000 x 1850 mm)
  - 2x Art. 32706 Airbag small (1000 x 1200 mm)
  - 4x Art. 32346 particle board large (2200 x 1033 x 10 mm)
  - 20x Art. 39121 particle board small (1080 x 860 x 10 mm)
- to be positioned on each pallet at lower level

## upper level 19 pallets

